

PVC COATED GRC 90° STANDARD ELBOWS

Description:


PVC Coated GRC 90° Standard Elbows are available in standard & special radius dimensions and in various degrees as required. All elbows are manufactured from Calbond PVC coated conduit and meet all applicable standards.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Specialized corrosion resistant coating provided on threads
- Sizes available are 1/2" to 6"
- Available in 90, 60, 45, and 30 degree bends

UL Listings Include:

- Calbond PVC coated conduit is UL/CUL listed in accordance to UL6 & ANSI C80.1 Standards
- Calbond PVC coated conduit is UL/cUL listed rigid ferrous metal conduit with polyvinyl chloride coating verified for PVC adhesion performance
- Calbond PVC coated conduit complies with NEMA RN-1
- UL File Number E226472



Item Number	Trade Size	Metric Size (mm)	Weight Per 100 (lbs)	Standard Radius A	Offset B	Tangent T
PV0590EL00	1/2"	16	70	4.25	6.0	1.7
PV0790EL00	3/4"	21	100	4.50	6.7	2.2
PV1090EL00	1"	27	190	5.75	8.0	2.4
PV1290EL00	1-1/4"	35	310	7.25	9.6	2.8
PV1590EL00	1-1/2"	41	400	8.25	10.6	2.6
PV2090EL00	2"	53	640	9.50	12.0	3.5
PV2590EL00	2-1/2"	63	1210	10.50	14.8	4.7
PV3090EL00	3"	78	1950	13.00	17.0	5.3
PV3590EL00	3-1/2"	91	2630	15.00	20.9	6.1
PV4090EL00	4"	103	3280	16.00	21.0	6.5
PV5090EL00	5"	129	6750	24.00	32.0	11.2
PV6090EL00	6"	155	10510	30.00	41.0	12.1