

PVC Coated 90° Standard Elbows

Calbond PVC coated elbows are available in standard & special radius dimensions and in various degrees as required. All elbows are manufactured from Calbond PVC coated conduit and meet all applicable standards.


Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 6"
- Available in 90, 60, 45, and 30 degree bends



UL listings and Compliances:

- Calbond PVC coated conduit is UL/CUL listed in accordance to UL6 & ANSI C80.1 Standards
- Calbond PVC coated conduit is UL/CUL listed rigid ferrous metal conduit with polyvinyl chloride coating verified for PVC adhesion performance
- Calbond PVC coated conduit complies with NEMA RN-1
- UL File Number E226472 & E230584



| Item Number | Trade Size | Size Metric (mm) | Weight Per 100 (lbs) | Standard Radius A | Offset B | Tangent T | Aluminum Item Number |
|-------------|------------|------------------|----------------------|-------------------|----------|-----------|----------------------|
| PV0590EL00 | 1/2" | 16 | 70 | 4.25 | 6.0 | 1.7 | PA0590EL00 |
| PV0790EL00 | 3/4" | 21 | 100 | 4.50 | 6.7 | 2.2 | PA0790EL00 |
| PV1090EL00 | 1" | 27 | 190 | 5.75 | 8.0 | 2.4 | PA1090EL00 |
| PV1290EL00 | 1-1/4" | 35 | 310 | 7.25 | 9.6 | 2.8 | PA1290EL00 |
| PV1590EL00 | 1-1/2" | 41 | 400 | 8.25 | 10.6 | 2.6 | PA1590EL00 |
| PV2090EL00 | 2" | 53 | 640 | 9.50 | 12.0 | 3.5 | PA2090EL00 |
| PV2590EL00 | 2-1/2" | 63 | 1210 | 10.50 | 14.8 | 4.7 | PA2590EL00 |
| PV3090EL00 | 3" | 78 | 1950 | 13.00 | 17.0 | 5.3 | PA3090EL00 |
| PV3590EL00 | 3-1/2" | 91 | 2630 | 15.00 | 20.9 | 6.1 | PA3590EL00 |
| PV4090EL00 | 4" | 103 | 3280 | 16.00 | 21.0 | 6.5 | PA4090EL00 |
| PV5090EL00 | 5" | 129 | 6750 | 24.00 | 32.0 | 11.2 | PA5090EL00 |
| PV6090EL00 | 6" | 155 | 10510 | 30.00 | 41.0 | 12.1 | PA6090EL00 |